Carina® Sensing System™
DATASHEET

Bringing you the best of both worlds: the engineered fibre optic sensing system combining the extensive, high density coverage of distributed sensors with sensitivity beyond that of point sensors.

The Carina Sensing System is a versatile fibre optic sensing system and comprises an advanced optoelectronics interrogator and sensing cables, which are equipped with the new family of engineered Constellation™ fibres; to gain two orders of magnitude lower noise floor (100x or 20dB improvement) over that achieved with standard fibres.



Performance				
Gauge length (software selectable)	25 cm	2 m	10 m	30 m
Sensing range*	15 km	30 km	50 km	60 km
1 kHz amplitude spectral density**	90 pε per sqrt Hz	3 pε per sqrt Hz	300 fε per sqrt Hz	70 fε per sqrt Hz
10 Hz dynamic range**	130 dB			
Sample spacing	25 cm to 32 m (40,000 samples maximum)			
Spatial resolution†	1 gauge length			
Sampling frequency††	25 Hz to 100 kHz			
Acoustic sensitivity	<0.001 Hz to 50 kHz			

* Defined for singlemode fibre.

** Median value for standard specification engineered Constellation™ fibre, with interrogator settings optimised for a 700 m fibre length.

† Defined as the spatial rise / fall length of an extended source. Spatial localisation of a point source is achievable down to 1 m for standard singlemode fibre and to half a gauge length for engineered Constellation fibre, apart from 25 cm gauge length where the spatial localisation limit is 25 cm.

†† Depending on the fibre length.

Silixa Ltd, Silixa House
230 Centennial Park, Centennial Ave,
Elstree, Hertfordshire WD6 3SN, UK
enquiriesUK@lunainc.com

Silixa LLC
3102 W Broadway St,
Missoula, MT 59808 USA
enquiriesMO@lunainc.com

Silixa LLC
16203 Park Row, Suite 185,
Houston TX 77084, USA
enquiriesTX@lunainc.com

SILIXA
A LUNA company
www.lunainc.com

I/O Connections

Fibre	1 x E2000/APC (singlemode or multimode fibre compatible)
Power	1 x IEC 60320-1 C20 inlet
Ethernet	2 x 1 GbE RJ45 port
USB	2 x USB 3.0 port and 4 x USB 2.0 port
Display	2 x DisplayPort
Internal data storage	1 x 4 TB SSD RAID module
External data storage connection	2 x 10 GbE SFP+ port and 2 x PCIe x4 cable port
GPS antenna input	1 x SMB connector
Synchronisation clock output	1 x SMB connector
Trigger	Trigger In: 1 x SMB connector, Trigger Out: 1 x SMB connector
PTP	1 x LAN RJ45 port

Electrical

Input voltage range	100 to 240 VAC
Input voltage frequency	50 to 60 Hz
Power consumption	215 W (typical)

Mechanical and Environmental

Dimensions	195 mm (with feet attached) x 444 mm x 518 mm (H x W x D)
Rackmount	1 x 19” Rack mount kit supplied
Weight	24.1 kg
Operating temperature range	5 °C to 40 °C
Operating relative humidity range	10% to 90%, non-condensing

Compliance

Laser safety	Class 1
Product marking	CE, UKCA and FCC

Silixa Ltd, Silixa House
230 Centennial Park, Centennial Ave,
Elstree, Hertfordshire WD6 3SN, UK
enquiriesUK@lunainc.com

Silixa LLC
3102 W Broadway St,
Missoula, MT 59808 USA
enquiriesMO@lunainc.com

Silixa LLC
16203 Park Row, Suite 185,
Houston TX 77084, USA
enquiriesTX@lunainc.com

SILIXA
A LUNA company
www.lunainc.com